

XT 7 GOOSENECK SERIES STANDARD FEATURES



Deck Width: 7'
 Length: 12', 14', 16'
 GVWR: 14,000 lbs
 Empty Weight: 5,320-5,580 lbs

Payload Capacity: 6.55 yd³-8.7 yd³
 Sides: 24" or 48" 11-GA, Fully Formed Sides, 10-GA Top Rail Measuring 2.75" x 4.25"
 Floor: 7-GA Smooth Floor

Frame: Mainframe 8" Ultra Strong I Beam Frame
 Fenders: Diamond Plate
 Door: **CoreLatch™ Locking System**

Coupler Height: 2-5/16" Adjustable, 6 Hole
 Tires: ST235/80 R16 LRE
 Axles: 7K or 8K Tandem Axles, Includes Electric Brakes

3" Channel Cross Members with 16" Spacings

24" or 48" Fully Formed Sides, 10-GA Top Rail Measuring 2.75" x 4.25"

Ultra-Low 27" Deck Height

Adjustable Dual Handle Spreader Gate & Barn Doors

6'5" **MegaStrength™** Ramps for Quick and Effortless Access



Actual Size Shown 7' x 16'

Massive 91.25" Wide Top Box For Maximum Capacity

17 Stake Pockets 1-5/8" x 3-1/2"

10" I Beam Gooseneck Frame

High-Capacity Hydraulic Scissor Lift

Lockable 5.4 Cu. Ft. Toolbox, with Charger, Pump Battery and Remote Control

Built-In Steel Side Step

16" 8-Hole Wheels

Multi-Leaf Suspension System with Equalizer Mechanism



RAMPS

6'5" **MegaStrength™** ramps are designed for quick and effortless access, providing a smooth and secure loading experience for all your heavy-duty needs.



LOCKING D-RINGS

Secure locking D-Rings ensure the door remains firmly open during loading and unloading, enhancing safety and convenience by preventing unexpected closures.



TARP

95" extra-wide tarp with a crank style roller offers full load coverage, easy operation, and better protection, making it versatile and compliant with regulations.



JACKS

2 - 12,000 lbs spring-loaded adjustable jack offers quick, easy adjustments for stable trailer leveling and hitching, providing reliable support for heavy loads with minimal effort.